

Teck Specialties

TECK POLYMER TECHNOLOGY

TECK 75

Fast Patch

Teck 75

- ◆ **Non-Gypsum Based**
- ◆ **Rapid Early Strength Gain**

Teck 75 is a fast setting, cement based, trowelable patching material. This material is especially suited for patching concrete floors, ramps, etc. Because of its fast setting characteristics, it is also frequently used in minimizing stepped areas in concrete slabs or establishing slopes that can be almost immediately overlaid with Teck 2800 or Teck 600.

Uses - Repairing uneven or distressed concrete floors, stairway treads and ramps.

Advantages - mixed with water only, installs from a feathered edge to 3/4" without adding fillers. After 15-30 minutes (dependent upon job condition) the surface can be finished with a steel trowel or cut trowel to desired smoothness. Most finished floor goods installations can begin after 90 minutes of Teck 75 application.

Limitation - Do not install Teck 75 where substrate is below 40°F or where the temperature will fall below 40°F within 24 hours of installation.

TECHNICAL/PHYSICAL DATA

Compressive Strength 3500 psi (ASTM-C-109) after 1 day	Initial Set 30 minutes (At 70° F)
Compressive Strength 5500 psi (ASTM-C-109) (28 days)	Final Set. 40 minutes (At 70° F)
Coverage 50 lb. bag - approx. 50 sq. ft. @ 1/8"	Mix Ratio 5.5 qts. water/bag

All tests are performed by independent laboratories.
Varying field conditions may yield slightly different results.

TOLL FREE 866 – NOW – TECK

Set Time (ASTM C 109)	
Final Set	40 Minutes

Compressive Strength (ASTM C 109)	
1 hour	1000 psi
1 day	3500 psi
7 days	4500 psi
28 days	5500 psi

Warranty

Warranty

Warning: Keep out of reach of children. If eaten or swallowed, serious personal injury could occur. Prolonged contact with skin may cause irritation. In case of eye contact, flood eyes repeatedly with water. Consult your physician under any of the above circumstances. This product is sold for commercial application by trained professionals only and not for consumer use or resale. Buyer has not relied on any representation made by Teck Specialties, Inc. but rather has conducted its own tests on the product to determine its suitability for use.

Limited Warranty:

Notwithstanding the above, Teck Specialties, Inc., warrants its product to be free from defects in the material for a period of one (1) year from the date of manufacture. It will replace any defective material, reserving the right to inspect the material prior to replacement. Buyers' full and exclusive remedy is the replacement of any defective product F.O.B. factory. Seller shall in no way be responsible for any incidental or consequential damage, including without limitation, damage for lost profits, business interruption, property damage, economic loss or injuries to the person. Seller shall not be liable to Buyer for contribution or indemnity or for other losses arising from the use of the product.

THERE ARE NO OTHER WARRANTIES EXPRESSED OR IMPLIED INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE.

To the extent that any part of this Limited Warranty or remedy is held invalid by a court of competent jurisdiction, it shall not affect remaining portions of the Limited Warranty.

©2002 Teck Specialties, Inc.

