

Teck Specialties

TECK POLYMER TECHNOLOGY **ULTRA SKIM TECK**

Cement Based Finishing Underlayment

Ultra Skim Teck

- ◆ **Cement Based**
- ◆ **Easy to trowel**
- ◆ **Add only water**
- ◆ **Install finished goods in 60 – 90 minutes**

Ultra Skim Teck is a fast setting cement based trowelable underlayment. It is designed to be used from an ultra thin skim coat to 1/2" in one pass and used to go over concrete or wood substrates, sheet goods, hard tiles, vinyl composition tile, cut back adhesives and other non-water soluble adhesives.

Advantages-Very smooth and creamy product. Provides good workability. Easy to trowel. Portland cement based, enhanced with polymers to promote maximum bonding to a variety of substrates. No primer needed – mix only with water.

Most floor coverings can be installed in 60 – 90 minutes. Prior to

installation substrate must be structurally sound, clean and solid, free of all dirt, oil, wax, grease and all other contaminants that could affect the bond. Ultra Skim Teck has a 12 month shelf life when stored in a cool dry place, unexposed to sunlight.

Coverage- One 10 pound pail of Ultra Skim Teck covers approx. 250-300 square feet depending upon the porosity of the substrate.

Mixing – Mix each 10 lb. pail with 2-1/2 quarts of water. Mix to a smooth, lump free, creamy consistency.

TECHNICAL DATA

Compressive Strength . . . (ASTM-C-109)
1 day 2200 psi
28 days 4700 psi

Working Time 20 minutes
(At 70° F)

Initial Set 25 – 30 minutes
(ASTM-C-191) (At 70° F)

Final Set 30 – 40 minutes
(At 70° F)

Times are estimates and can vary according to ambient and substrate temperature.

Precautions- Ultra Skim Teck for interior use only and should not be applied over gypsum, foam or metal substrates. Do not over water. Mix only enough material that can be finished in 15 – 20 minutes.

TOLL FREE 866 – NOW – TECK

Cement Based Finishing Underlayment

Warranty

Warranty

Warning: Keep out of reach of children. If eaten or swallowed, serious personal injury could occur. Prolonged contact with skin may cause irritation. In case of eye contact, flood eyes repeatedly with water. Consult your physician under any of the above circumstances. This product is sold for commercial application by trained professionals only and not for consumer use or resale. Buyer has not relied on any representation made by Teck Specialties but rather has conducted its own tests on the product to determine its suitability for use.

Limited Warranty:

Notwithstanding the above, Teck Specialties, warrants its product to be free from defects in the material for a period of one (1) year from the date of manufacture. It will replace any defective material, reserving the right to inspect the material prior to replacement. Buyers' full and exclusive remedy is the replacement of any defective product F.O.B. factory. Seller shall in no way be responsible for any incidental or consequential damage, including without limitation, damage for lost profits, business interruption, property damage, economic loss or injuries to the person. Seller shall not be liable to Buyer for contribution or indemnity or for other losses arising from the use of the product.

THERE ARE NO OTHER WARRANTIES EXPRESSED OR IMPLIED INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE.

To the extent that any part of this Limited Warranty or remedy is held invalid by a court of competent jurisdiction, it shall not affect remaining portions of the Limited Warranty.

©2002 Teck Specialties

Teck Specialties